FR-I0 Series

For Cylinder Single-Stage Pressure Regulator


Specifications


25MPa
14.8MPa or less
0.15 or 0.2MPa
W22-14 O.R.

Outlet Connection	Hose Nipple 8.5mm
Accessories	Gasket Packing(Fiber)×2Pcs
Approximate Weight	1.2kg



Outline drawing






[Note]

■ Unit: mm ■ Dimentions are subject to

change without notice.

Flow characteristics



Materials of construction

Body	C3604 BD
Bonnet	ZDC
Poppet	C3604BD
Seat	NBR
Diaphragm	NBR
Safety valve seat	NBR

[Note]■ These tests were performed at ambient conditions.

List of specifications

Series	Inlet Pressure Gauge MPa	Outlet Pressure MPa	Inlet Connection	Outlet Connection
FR-IO	25	0.15	W22 (R)	Hose Nipple 8.5 mm
	25	0.2	W22 (R)	Hose Nipple 8.5 mm
	25	0.25	W22 (R)	Hose Nipple 8.5 mm
	25	0.15	W21 (L)	Hose Nipple 8.5 mm
	25	0.2	W21 (L)	Hose Nipple 8.5 mm
	25	0.25	W21 (L)	Hose Nipple 8.5 mm